

# nora liquid wax

A solvent free wax emulsion used as a separation layer, ensuring excess weld does not bond to the flooring surface when cold welding nora® floor coverings.

## **Product Construction Specifications**

Product: nora® liquid wax, Article 109914

Material Composition: A solvent-free wax emulsion.

Material Description/Size: 16-ounce white plastic bottle.



## **Performance Standards**

Shelf Life:	Use within 12 Months of opening
Application:	Clean cloth
Coverage:	~ 675 ft at 4 in wide
Dry Time:	~ 5-10 minutes
Freeze/Thaw stable:	Stable per ASTM D7149 at 0°F (- 18°C)

## **Health + Environmental Specifications**

Material Composition: Free of organic solvents, formaldehyde, asbestos, lindane, rosins, phthalates, or any other volatile components.

## **Installation**

Site Conditions: The installation area must be fully enclosed, weather tight, and climate controlled between 63°F and 75°F and 40% to 60% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after installation.

Unique Characteristics:

- Non-flammable and freeze/thaw stable
- Used as a release agent prior to the cold welding of norament® flooring
- Can also be used as a separation layer on tools and adhesive trowels

For complete installation instructions refer to the nora Installation Instructions.

## **Disclaimer**

It is the user's responsibility to read, understand and follow the nora Installation Instructions, Product Data Sheet, and Safety Data Sheet available on [www.nora.com](http://www.nora.com). You should comply with all applicable OSHA, local, state, and federal regulations.

## **Clean-up**

Removed during initial cleaning: To remove nora liquid wax from nora flooring coverings after the nora® cold weld is fully cured, wet mop the floor using a high-pH cleaner (12–13pH) solution diluted as per the manufacturer's mixing instructions. Allow the solution a minimum dwell time of 10 minutes. Scrub the floor thoroughly with a floor scrubber as outlined in the nora Maintenance Guidelines.

## **Storage**

Room temperature and away from direct sunlight.

## **Disposal**

Dispose in accordance with local, state, and national regulations. Where possible, collect product residues and reuse. Do not allow product to get into drains, watercourses, or landfill. Collect any remaining waste material, mix both components and allow to harden, and then dispose of as Construction Waste.

## **Warranty**

Refer to the nora Limited Warranty - Americas.

Current nora Installation Instructions, Guide Specifications, Maintenance Guidelines, and Limited Warranties can be found at [www.nora.com](http://www.nora.com).

nora®, norament®, and noraplan® are trademarks owned by nora systems GmbH and registered in the United States, Canada, and other countries. All other trademarks are the property of their respective owners.

Updated: April 2024